SERIE 44 – ELECTRON

* IL POMELLO FUORIESCE E RIENTRA AUTOMATICAMENTE
* KNOB COMES OUT AND RE-ENTERS AUTOMATICALLY

COSTRUZIONE RINFORZATA

Porta acciaio 8 mm, spessore totale 55 mm, tagliata laser. Apertura a tutta luce, cerniera a tutta altezza. Battute a Uspessore 4 mm antisfondamento. Catenacci Ø 25 cromati, indipendenti, girevoli, montati su doppio supporto 4+4 mm. Serrature corazzate con piastra di rinforzo in acciaio al manganese. Robuste saldature robotizzate. Coperchio interno imbutito, smontabile solo a serratura aperta. Corpo 2 mm saldato a tratto continuo. Parete posteriore 3 mm. ***Art. 4443 – 4444 : Esecuzione senza pomello, con molla apriporta**

CONGEGNO di CHIUSURA

Sistema a combinazione elettronica digitale, testato **CE**. 111.111.000 variazioni possibili, movimento a motore. Alimentazione a batteria 6V(4 pile Stilo LR6 AA 1,5V), possibilità di alimentazione d'emergenza (pila 9V 6LR61). Processore Low-Power tecnologia basso consumo.
Test di manipolazione, blocco antimanipolazione, combinazione base 00.00.00 (6 ZERI).
A richiesta : Versione con Codice D'emergenza tipo Hotel (di serie S.78) Versione con Apertura Ritardata programmabile .

REINFORCED CONSTRUCTION

Laser-cut steel door, 8mm (total thickness 55mm) Full-light opening, full-height hinge. 4 mm thickness, U-shaped, anti-smashing rabbets.Chromium-plated, independent, turning bolts, Ø25 mm, mounted on double support 4+4 mm. Armoured locks protected by a reinforcement-plate in manganese-steel material. Strong robotized weldings. Internal deep-drawn cover, it can be dismantled just when lock is open. 2 mm body welded by continual wire. 3 mm of back-wall. ***Art. 4443 – 4444 : Without knob with door-opener spring.**

CLOSING SYSTEM

Digital electronic combination, system **CE** tested. 111.111.000 effective variations, motorized. Alimentation: 6V battery (4 x 1,5V—LR6 AA), external supply possibility (9V battery LR61). Low-Power processor (low consumption technology). Manipulation Test, anti-manipulation block. Basic combination : 00.00.00 (6 zeros) On request : Emergency-Code Version, like for Hotel use (of standard production on Mod.78) or programmable Time-Delay-Version.

44		DIMNESIONI mm						LUCE PORTA DOOR OPENING		CATENACCI BOLTS	RIPIANI SHELVES	PESO WEIGHT
		ESTERNE / OUTSIDE			INTERNE / INSIDE							
ART.	N.	H/H	L/W	P/D	H/H	L/W	P/D	H/H	L/W			Kg
4422	3	235	365	142	212	346	84	156	272	2	1	15,1
4423				192			134				1	16,3
4433	3A	235	365	192	272	346	134	156	272	2+2	1	19,4
4443	4V	415	365	192	392	246	134	336	172	2	1	21,0
4444				242			184		272			22,1
4453	4A	335	415	192	312	396	134	256	322	3+2	1	24,3
4454				242			184				1	25,6
4455				292			234				1	28,4
4473	6V	515	365	192	492	346	134	436	272	3+2	2	31,7
4474				242			184				2	33,4
4475				292			234					25,1

JUWEL SRL Via I Maggio 3/e 20010 Vanzago (MILANO) – Italy – WEB www.juwel.it Email info@juwel.it