SERIE 62/0– ELEGANCE

CHIAVE INESTRAIBILE A SERRATURA APERTA
UNREMOVABLE KEY WHEN LOCK IS OPEN

CERTIFICATA EN 1300 B CERTIFIED

COSTRUZIONE RINFORZATA

Porta acciaio 8 mm (spessore totale 55 mm), tagliata a laser. Pareti doppie (3 + 19,5 + 1,5 = 24 mm) Porta e Pareti con materiale di protezione (lana di roccia) non combustibile . Chiusura sui tre lati con catenacci Ø 25 cromati . Robuste saldature robotizzate.
Adatta per raccoglitori A4. Fori di fissaggio Ø 9,5 mm, sul dorso e alla base.

CONGEGNO di CHIUSURA
Serratura a 8 leve effettive antimanipolazione, 2 mandate. Chiavi bicifrate (48.017.788 variazioni effettive) **Congegno Certificato a Norma Europea EN 1300 Classe B.**

REINFORCED CONSTRUCTION

Laser-cut steel door, 8 mm (total thickness 55mm) Double-walls (3+19,5+1,5 = 24 mm). Door and walls with insulating protection material (rock wool), not combustible. Lock on 3 sides by chromium-plated bolts,Ø25 mm. Strong robotized weldings.
Suitatable for A4 file-holders. Fixing holes (Ø 9,5 mm) at rear wall and base.

CLOSING SYSTEM
Antimanipulation lock, 8 effective levers, 2 turns. Bicyphered keys (48.017.788 effective variations). **Device certified according to European Norm EN 1300 Class B**.

62/0	DIMENSIONI mm							LUCE PORTA *DOOR OPENING*		CATENACCI *BOLTS*	RIPIANI *SHELVES*	PESO *WEIGHT*
		ESTERNE / *OUTSIDE*			INTERNE / *INSIDE*							
ART.	N.	H/H	L/W	P/D	H/H	L/W	P/D	H/H	L/W			Kg
6230	3	315	415	378	250	353	300	246	323	2+2	1	37,8
6240	4	415			350			346		2+2	1	45,3
6250	5	610			545			541		2+2	1	60,6