SERIE 68/4 – ELECTRON – DEPOSAFE

CON FESSURA (218x10mm) PER INTRODUZIONE DENARO.
APERTURA RITARDATA PROGRAMMABILE DA 0 A 99 MINUTI.

WITH DEPOSIT-SLOT FOR INTRODUCING MONEY(218x10mm).
ANTI-ROBBERY ELECTRONIC-SYSTEM (TIME-DELAY OPENING, PROGRAMMABLE FROM 00 TO 99 MINUTES).

IL POMELLO FUORIESCE E RIENTRA AUTOMATICAMENTE
KNOB COMES OUT AND RE-ENTERS AUTOMATICALLY

COSTRUZIONE RINFORZATA

Porta acciaio 8 mm, spessore totale 55 mm, tagliata laser. Apertura a tutta luce, cerniera a tutta altezza. Battute a U spessore 4 mm antisfondamento. Catenacci Ø 25 cromati, indipendenti, girevoli, montati su doppio supporto 4+4 mm. Serrature corazzate con piastra di rinforzo in acciaio al manganese. Robuste saldature robotizzate. Coperchio interno imbutito, smontabile solo a serratura aperta. Corpo a pareti singole 5 mm. Fori Ø12 di fissaggio al dorso e alla base.

CONGEGNO di CHIUSURA

Sistema a combinazione elettronica digitale, testato **CE**. 111.111.000 variazioni possibili, movimento a motore. Alimentazione a batteria 6V(4 pile Stilo LR6 AA 1,5V), possibilità di alimentazione d'emergenza (pila 9V 6LR61). Processore Low-Power tecnologia basso consumo.
Test di manipolazione, blocco antimanipolazione, combinazione base 00.00.00 (6 ZERI).

REINFORCED CONSTRUCTION

Laser-cut steel door, 8 mm (total thickness 55mm) Full-light opening, full-height hinge. U-shaped, anti-smashing rabbets (4 mm). Chromium-plated, independent, turning bolts, Ø25 mm, mounted on double support 4+4 mm. Armoured locks protected by a reinforcement-plate in manganese-steel material. Strong robotized weldings. Internal deep-drawn cover, it can be dismantled just when lock is open. 5 mm single-wall body. Fixing holes (Ø 12 mm) at rear and base.

CLOSING SYSTEM

Digital electronic combination, system **CE** tested. 111.111.000 effective variations, motorized. Alimentation: 6V battery (4 x 1,5V—LR6 AA), external supply possibility (9V battery LR61). Low-Power processor (low consumption technology). Manipulation Test, anti-manipulation block. Basic combination : 00.00.00 (6 zeros)

68/4		DIMENSIONI mm						LUCE PORTA DOOR OPENING		CATENACCI BOLTS	RIPIANI SHELVES	PESO WEIGHT
		ESTERNE / OUTSIDE			INTERNE/ INSIDE							
ART.	N.	H/H	L/W	P/D	H/H	L/W	P/D	H/H	L/W			Kg
6824	3A	305	375	290	295	365	226	216	272	2	-	32,8
6874	6V	610	410	380	600	400	316	436	272	3+2	1	66,1